



Chief Safety Officer Decision
(Application for Substitution, Equivalency, or Exemption)

Date: 2020-Jun-04 | 12:31:01 PM NDT

C-NLOPB Reference: 2020-RQ-0075

Applicant: TechnipFMC

Applicant Reference: 076766C001-RQF-23

Installation Name: DSV-Deep Explorer

Authority: *Canada-Newfoundland and Labrador Atlantic Accord Implementation Act, subsection 151(1) & section 205.069*

Canada-Newfoundland and Labrador Atlantic Accord Implementation Newfoundland and Labrador Act, subsection 146(1) and section 201.66

Regulation: Section 56(10)(13)58(4)(7)(8)(12)(a) of the *Newfoundland Offshore Petroleum Installations Regulations*


Decision:

The Chief Safety Officer approves the Applicant's, the owner of the *DSV-Deep Explorer*, proposal to use the *International Load Line Convention for Watertight Integrity* and *DNV Rules for Classification of Ships Part 3; Chapter 3, Section 6 Opening and Closing Appliances and Section 9 Stability and the IMO Intact Stability Code* in lieu of Section 56(10)(13)58(4)(7)(8)(12)(a) of the *Newfoundland Offshore Petroleum Installations Regulations*, which lists various requirements for stability and watertight integrity of floating platforms.

This Decision is effective from the date of issuance herein until the earlier of:

- a) the date a Regulation referenced herein is repealed or the date a particular subsection that is the object of a substitution or exemption being granted hereby is amended or replaced, or
- b) the date on which the CSO and /or CCO (as applicable) revokes this Decision as a result of i) any enforcement action by the Board related to this Decision or ii) new information or analysis coming to light challenging the assessment upon which this Decision was based, including but not limited to any changes to commitments made by the Applicant in its application.

For greater certainty, the Chief Safety Officer will no longer have authority under the Accord Acts to grant exemptions for Part III.1 transitional regulations once they are repealed.

DocuSigned by:


Chief Safety Officer